



» The Essential POS Enabler »

E-PoS Customer Pole Display

VFD2600 Display

Information at every stage of the consumer journey

- EPSON emulation compatible, Support Chinese character & graphic displaying
- 3 level pole for length adjusting, Adaptor of wide power input range
- Aluminum housing and fanless design.
- Customized main board with few cable connections makes neat frame



Low Noise	Various Interfaces	Cash Drawer Driver	Easy-Loading
Easy to use	Strong Compatibility	High Speed	Auto Cutter

Hospitality	Retail	Car Parking Systems
-------------	--------	---------------------

SPECIFICATIONS: E-PoS VFD2600

Display Method:	Vacuum Fluorescent Display	COM Port (Optional):	Baud rate from 2400BPS to 19200BPS (9600BPS as default)
Display Type:	24(Lines) x 120(Columns)	Power:	DC 12V, 1A
Language Supported:	English	Power Consumption:	<4W
Characters Font	10 Characters/line (Font: 12X12) 20 Characters/line (Font: 6X12)	Weight:	1.0kg
Character Set:	96 ASCII	Height Supported:	170mm, 170+120mm, 170+120+120mm
Emit Color:	Green	Display Panel Sizes:	206x118x283mm
Drive Mode:	Dynamic	Display Base Sizes:	206x118x403mm
Audio:	No	Package Sizes:	206x118x523mm
Emulation:	EPSON, Nortriake, futaba, PL-200, UTC Standard, ENHANCE, AEDEX, ADM788, DSP800, CD5220 (PTC),- LOGIC, POS7300, UTC, EMAX	Environment:	Work Temp. and Humidity: -10-55°C, 35-85%RH / Storage Temp. and Humidity: -20-65°C, 10-85%RH
Elevation:	0-90 °		
Ports:	1x USB, 1XRS232 (Optional)		



Partner Tech Middle East Group

SALES OFFICE: Office No. 1004, 10th Floor, Aspect Tower, 33a Happiness Street, Business Bay, Dubai, UAE
 TECHNICAL & WAREHOUSE: Plot S10119, Gate 7, South Zone, Jebel Ali, Dubai, UAE
 SALES: +971 4 447 4273 | TECHNICAL & WAREHOUSE: +971 4 886 2980
 SALES: info@partnertechme.com | TECHNICAL SUPPORT: support@partnertechme.com



Download Our APP

Distribution Brands

